


MATHEMATICAL MODELLING OF CONVECTIVE FLOW OVER A HORIZONTAL CIRCULAR CYLINDER WITH CONVECTIVE BOUNDARY CONDITIONS IN VISCOUS, MICROPOLAR AND NANOFUID

NORHAFIZAH BINTI MD SARIF

DOCTOR OF PHILOSOPHY
UNIVERSITI MALAYSIA PAHANG




SUPERVISOR'S DECLARATION

I hereby declare that I have checked this thesis and in my opinion, this thesis is adequate in terms of scope and quality for the award of the degree of Doctor of Philosophy.

(Supervisor's Signature)

Full Name : DR. MOHD ZUKI BIN SALLEH
Position : ASSOCIATE PROFESSOR
Date : DECEMBER 2018



STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citation which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

(Author's Signature)

Full Name : NORHAFIZAH BINTI MD SARIF
ID Number : PSE12001
Date : DECEMBER 2018

MATHEMATICAL MODELLING OF CONVECTIVE FLOW OVER A HORIZONTAL
CIRCULAR CYLINDER WITH CONVECTIVE BOUNDARY CONDITIONS IN
VISCOUS, MICROPOLAR AND NANOFLUID

NORHAFIZAH BINTI MD SARIF

Thesis submitted in fulfilment of the requirements
for the award of the degree of
Doctor of Philosophy

Faculty of Industrial Sciences & Technology
UNIVERSITI MALAYSIA PAHANG

DECEMBER 2018

**If I were to have kids one day, this is for them. I want them to know that once, their
mom had a dream like they do**

ACKNOWLEDGEMENTS

In the name of Allah, the Most Gracious, the Most Merciful

Alhamdulillah, all praise belongs to Allah for His guidance and for giving me the strength to finish this arduous study. The journey to complete the study is not always smooth as laminar flow. Unpredictable things occur just like a turbulence flow and making life extra complicated to handle. But I believe, the more turbulent your journey, the sweeter your reward. Therefore, I am grateful to Him for all tests and trials befall upon me, and I am sure that without His help, this thesis would not have been possible.

The entire output of this thesis are not my work alone. There are exceptional individuals around me that have made it easier for me to finish my writing. First and foremost, I would like to take this opportunity to express my immeasurable appreciation to my supervisor Assoc. Prof. Dr. Mohd Zuki Bin Salleh for his assistance, continuous support and encouragement throughout this period of my study. I am genuinely moved by his understanding and tolerance of my silly mistakes. Besides him, my external supervisor Prof. Dr. Roslinda Binti Mohd Nazar also played a vital role throughout completion of this thesis. I wish to extend my gratitude to her for the helpful suggestions and for spending time checking my work and monitoring my progress despite her busy schedule.

I wish to express my love to my mother Pn. Saadiah Binti Any who had never ceased to provide emotional support and motivational words for me. She is always there whenever needed support. Her unconditional love and patience is my pillar of strength. Special thanks go to my siblings for always believing in me and for keep reminding me that 'there is always a light at the end of the tunnel'.

I gratefully acknowledge the funding source of my PhD from Universiti Malaysia Pahang and the Ministry of Higher Education which approved my study leave and awarding SLAI scholarship to me. Finally, I would like to thanks, everyone who has been involved directly or indirectly in the preparation of this thesis.

ABSTRAK

Aliran bendalir dan pemindahan haba merupakan faktor penting dalam proses industri, pembuatan dan aplikasi kejuruteraan. Oleh sebab itu, adalah sangat perlu untuk memodelkan sistem bagi meningkatkan proses aliran bendalir dan pemindahan haba di mana kualiti akhir bagi sesuatu produk adalah bergantung kepada aliran kinematik serta pemanasan dan penyejukan secara serentak. Walau bagaimanapun, permasalahan matematik untuk aliran bendalir dan pemindahan haba terutamanya bagi geometri berbentuk silinder bulat mengufuk adalah sangat rumit untuk diselesaikan disebabkan wujudnya persamaan tak linear berpasangan. Bagi mendapatkan persamaan tepat, ia memerlukan masa yang lama dan usaha yang banyak manakala untuk menyediakan alat eksperimen pula memerlukan kos yang tinggi. Dalam kes ini, teknik berangka membuka jalan dalam mendapatkan penyelesaian terbaik untuk menyelesaikan masalah. Oleh itu, persamaan menakluk bagi aliran bendalir dan pemindahan haba beserta dengan syarat sempadan diselesaikan secara berangka. Kebiasaannya apabila model aliran olakan dilaksanakan, kebanyakan penyelidik menggunakan suhu dinding malar atau fluks haba malar sebagai syarat sempadan. Walau bagaimanapun, syarat sempadan ini tidak cukup lengkap untuk menggambarkan keadaan proses pemanasan bagi sesetengah keadaan dalam industri. Terdapat satu lagi jenis syarat sempadan yang telah diperkenalkan di mana permukaan bawah silinder dipanaskan dengan olakan dan ini dikenali sebagai syarat sempadan olakan. Dimotivasikan oleh syarat sempadan yang baharu ini, skema berangka yang dibangunkan dalam kajian ini diharap dapat dijadikan sebagai teori rujukan kepada penyelesaian tepat atau kepada kerja makmal di masa hadapan. Oleh itu, lima masalah berbeza bagi aliran bendalir dan pemindahan haba telah dipertimbangkan dalam kajian ini dengan mengambil kira syarat sempadan olakan sebagai pemanasan haba. Semua model matematik ini kemudiannya diterbitkan bagi kes aliran olakan paksaan, bebas dan juga campuran di atas silinder bulat mengufuk di dalam tiga jenis bendalir berbeza iaitu likat, mikrokutub dan juga nanobendalir. Persamaan menakluk pembezaan separa parabola yang menerangkan tentang aliran kemudiannya ditukar kepada penjelmaan ketakserupaan, dan kemudiannya diselesaikan secara berangka menggunakan kaedah teknik pembezaan terhingga yang stabil tanpa syarat dikenali sebagai kaedah kotak-Keller. Kod berangka dalam bentuk atur cara komputer dibina menggunakan perisian MATLAB. Penyelesaian berangka terdiri daripada profil halaju, suhu, isipadu pecahan nanozarah, geseran permukaan, dan perubahan haba bagi nilai parameter yang berbeza untuk keadaan fizikal bagi parameter olakan, olakan campuran, nombor Lewis, parameter poros dan juga nombor Prandtl. Didapati, bagi kes semua masalah yang dipertimbangkan, profil halaju dan suhu meningkat bagi peningkatan syarat sempadan olakan. Bagi kes nanobendalir, profil isipadu pecahan nanozarah turut meningkat jika syarat sempadan olakan meningkat. Begitu juga bagi setiap kenaikan parameter olakan, pekali geseran permukaan juga meningkat kecuali bagi kes nanobendalir, di mana jika parameter olakan menurun, ia menunjukkan penurunan bagi kedua-dua kes; Tiwari dan Das serta Buongiorno. Manakala, bagi pekali perubahan haba dan Nusselt number, dapat diperhatikan bahawa kesan parameter olakan meningkat secara signifikan. Kesimpulannya, dengan menggunakan syarat sempadan olakan terhadap silinder bulat mengufuk, didapati bahawa trend yang diperolehi bagi kes sempadan olakan adalah menyerupai kes suhu permukaan malar apabila nilai parameter sempadan olakan $\gamma \rightarrow \infty$.

ABSTRACT

Fluid flow and heat transfer play a significant factor in industrial processes, manufacturing and engineering applications. Therefore, a model is needed to enhance the process of fluid flow and heat transfer, as the final products are heavily reliant upon the kinematics of the flow and the simultaneous heating or cooling. However, the mathematical description of fluid flow and heat transfer specifically in geometry of horizontal circular cylinder are quite difficult to solve due to the nonlinearity existence and coupled equations. Indeed, obtaining an analytical solution requires additional effort and time meanwhile to setup an experiment is costly. In such a case, numerical methods provide means to solve the problem. Therefore, the governing equation of fluid flow and heat transfer together with the boundary conditions are solved numerically. Normally when modelling convection flow, many researchers applied constant wall temperature or constant heat flux in the boundary conditions. Nevertheless, these types of boundary conditions appear insufficient to adequately describe the heating process for some cases. Another type of boundary condition; where convection heats the bottom surface of the cylinder are applied in this study. This type of heating process is called convective boundary condition. Motivated by this newly type of boundary condition, the numerical scheme derived in this research is anticipated to provide a theoretical reference to other analytical solution or for future experimental work. Five different problems of fluid flow and heat transfer have been considered by incorporating convective boundary conditions as thermal heating. Accordingly, these mathematical models are then derived for steady laminar forced, free, and mixed convection boundary layer flows over a horizontal circular cylinder immersed in three types of fluid namely viscous, micropolar fluid and nanofluid. The governing parabolic partial differential equations describing the flow are transformed using non-similar transformation, which is then solved numerically using the unconditionally stable implicit finite difference scheme known as the Keller-box method. The numerical codes in the form of computer programmes are developed using MATLAB software. The numerical results obtained consists of velocity, temperature, nanoparticle volume fraction profiles, skin friction and heat transfer for various parameters of physical conditions such as convective, mixed convection, Lewis number, porosity parameters, as well as Prandtl number. It was observed that in all considered problems, the profiles of velocity and temperature profiles increase for increased values of convective boundary conditions. In the case of nanofluids, the values of nanoparticle volume fraction profile increases with with the increment on the values of convective boundary condition. Correspondingly, as the value of convective parameter increases, the skin friction coefficient increase as well except for nanofluid where the convective parameter decreased in both cases; Tiwari and Das, and Buongiorno. However for heat transfer coefficient and Nusselt number, it was observed that the effects of convective parameter has increased significantly. In conclusion, by applying the convective boundary condition over a horizontal circular cylinder, it is found that the trend of the solutions obtained for the convective boundary condition case is similar to the constant wall temperature case, especially when convective parameter $\gamma \rightarrow \infty$.

TABLE OF CONTENT

DECLARATION	
TITLE PAGE	i
ACKNOWLEDGEMENTS	ii
ABSTRAK	iii
ABSTRACT	iv
TABLE OF CONTENT	v
LIST OF TABLES	x
LIST OF FIGURES	xi
LIST OF SYMBOLS	xvi
LIST OF ABBREVIATIONS	xix
 CHAPTER 1 INTRODUCTION	 1
1.1 Research Background	1
1.2 Problem Statement	4
1.3 Research Objectives	5
1.4 Research Scope	6
1.5 Significance of Research	6
1.6 Overview of the Thesis	7
 CHAPTER 2 LITERATURE REVIEW	 8
2.1 Introduction	8
2.2 Basic Concept of Flow and Heat Transfer	8
2.2.1 Convective Heat Transfer	9

2.2.2	Boundary Layer Theory	10
2.2.3	Type of Fluids	12
2.2.4	Convective Boundary Conditions	15
2.3	Keller-box Method	16
2.4	Forced Convection Viscous Fluid	17
2.5	Free Convection Micropolar Fluid	20
2.6	Mixed Convection Viscous Fluid	22
2.7	Mixed Convection Nanofluid : Tiwari and Das Model	24
2.8	Mixed Convection Nanofluid : Buongiorno Model	26
CHAPTER 3 PROBLEM FORMULATIONS AND NUMERICAL METHOD		34
3.1	Introduction	34
3.2	Problem Formulations	35
3.2.1	Conservation of Mass	35
3.2.2	Conservation of Momentum	37
3.2.3	Conservation of Energy	41
3.2.4	Conservation of Nanoparticle	47
3.2.5	Governing Equations	48
3.2.6	Boundary Conditions	49
3.2.7	Boundary Layer Approximation	50
3.2.8	Non-Dimensional Variables	54
3.2.9	Non-Similar Transformation	55
3.3	Keller-box Scheme	56
3.3.1	First Order System	57
3.3.2	Finite Difference Method	58
3.3.3	Newton's Method	62

3.3.4	Block Elimination Technique	68
3.4	Initial Conditions	77
3.5	Initial Profile	78

CHAPTER 4 FORCED CONVECTION BOUNDARY LAYER FLOW OVER A HORIZONTAL CIRCULAR CYLINDER IN A VISCOUS FLUID 82

4.1	Introduction	82
4.2	Mathematical Formulation	83
4.3	Results and Discussion	86
4.4	Conclusions	93

CHAPTER 5 FREE CONVECTION BOUNDARY LAYER FLOW OVER A HORIZONTAL CIRCULAR CYLINDER IN A MICROPOLAR FLUID 94

5.1	Introduction	94
5.2	Mathematical Formulation	95
5.3	Results and Discussion	99
5.4	Conclusions	108

CHAPTER 6 MIXED CONVECTION BOUNDARY LAYER FLOW OVER A HORIZONTAL CIRCULAR CYLINDER IN A VISCOUS FLUID 110

6.1	Introduction	110
6.2	Mathematical Formulation	111
6.3	Results and Discussion	114
6.4	Conclusions	121

CHAPTER 7 MIXED CONVECTION BOUNDARY LAYER FLOW OVER A HORIZONTAL CIRCULAR CYLINDER IN A NANOFLUID : TIWARI AND DAS MODEL	123
7.1 Introduction	123
7.2 Mathematical Formulation	124
7.3 Results and Discussion	128
7.4 Conclusions	138
 CHAPTER 8 MIXED CONVECTION BOUNDARY LAYER FLOW OVER A HORIZONTAL CIRCULAR CYLINDER IN A NANOFLUID : BUONGIORNO MODEL	 139
8.1 Introduction	139
8.2 Mathematical Formulation	140
8.3 Results and Discussion	142
8.4 Conclusions	154
 CHAPTER 9 CONCLUSION	 156
9.1 Summary of Research	156
9.2 Suggestion for Future Research	159
REFERENCES	161
 APPENDIX A LIST OF SYMBOLS IN MATLAB PROGRAM	 173
 APPENDIX B MATLAB PROGRAM	 174
 APPENDIX C FORMULATION OF FORCED CONVECTION IN VISCOUS FLUID	 184
 APPENDIX D FORMULATION OF FREE CONVECTION IN MICROPOLAR FLUID	 188

APPENDIX E FORMULATION OF MIXED CONVECTION IN VISCOUS FLUIDS	193
APPENDIX F FORMULATION OF MIXED CONVECTION IN A NANOFLUID: TIWARI AND DAS MODEL	197
APPENDIX G FORMULATION OF MIXED CONVECTION IN A NANOFLUID: BUONGIORNO MODEL	201
APPENDIX H LIST OF PUBLICATIONS	206

LIST OF TABLES

Table 2.1	Development of forced convection in viscous fluid	29
Table 2.2	Development of free convection in micropolar fluid	30
Table 2.3	Development of mixed convection in viscous fluid	31
Table 2.4	Development of mixed convection : Tiwari and Das model	32
Table 2.5	Development of mixed convection : Buongiorno model	33
Table 3.1	Analysis order of magnitude for momentum equation Buongiorno model of nanofluids	51
Table 3.2	Analysis order of magnitude for energy equation Buongiorno model of nanofluids	52
Table 3.3	Analysis order of magnitude for nanoparticle volume fraction equation Buongiorno model of nanofluids	53
Table 4.1	Values of the reduced skin friction coefficient at some positions x when $\gamma = 1.0$	87
Table 4.2	Values of heat transfer coefficient Q_w when $Pr = 1.0$	87
Table 5.1	Comparison for the local Nusselt number Nu for the Newtonian case when $\gamma \rightarrow \infty$ (CWT)	99
Table 6.1	Comparison results for the heat transfer coefficient with $Pr = 1.0$, $\lambda = -1, 0, 1$ and $\gamma \rightarrow \infty$	114
Table 7.1	Thermophysical properties of fluid and nanoparticles	128
Table 7.2	Values of the the local Nusselt number $Re_x^{-1/2} Nu$ for $\phi = 0$ $Pr = 1.0$, $\gamma \rightarrow \infty$ and various values of λ	129
Table 8.1	Values of heat transfer coefficient $-\theta'(0)$ in viscous fluid	143
Table 8.2	Values of the dimensionless skin friction, heat flux and mass flux for various values of λ	144

LIST OF FIGURES

Figure 2.1	Boundary layer region	10
Figure 2.2	Separation of boundary layer	12
Figure 2.3	Physical model of nanofluids	14
Figure 3.1	Net rectangle for difference approximation	58
Figure 3.2	Flow diagram for Keller-box method	80
Figure 3.3	Flow chart of solution procedure	81
Figure 4.1	Physical model and coordinate system	83
Figure 4.2	Variation of the local skin friction coefficient $C_f(x, 0)$	88
Figure 4.3	Variation of the local heat transfer coefficient for various values of Pr	89
Figure 4.4	Variation of the local heat transfer coefficient for various values of γ	89
Figure 4.5	Velocity profiles $f'(y)$ near the lower stagnation point of the cylinder, $x \approx 0$	90
Figure 4.6	Temperature profiles $\theta(y)$ near the lower stagnation point of the cylinder, $x \approx 0$ when $\gamma = 1.0$	90
Figure 4.7	Temperature profiles $\theta(y)$ near the lower stagnation point of the cylinder, $x \approx 0$ when Pr = 1.0	91
Figure 4.8	Variation of the wall temperature $\theta(x, 0)$ at the lower stagnation point of the cylinder $x \approx 0$ with Prandtl number when $\gamma = 0.5$ and 1.0	91
Figure 4.9	Variation of the wall temperature $\theta(x, 0)$ at the lower stagnation point of the cylinder $x \approx 0$ with convective parameter γ when Pr = 0.72, 1.0 and 7.0	92
Figure 5.1	Physical model and coordinate system	95
Figure 5.2	Variation of the skin friction coefficient C_f for Pr = 7.0, $K = 1$ and various values of γ	100
Figure 5.3	Variation of the heat transfer coefficient Q_w for Pr = 7.0, $K = 1$ and various values of γ	100
Figure 5.4	Variation of the skin friction coefficient C_f for Pr = 7.0, $\gamma = 0.1$ and various values of material parameter K	102
Figure 5.5	Variation of the heat transfer coefficient Q_w for Pr = 7.0, $\gamma = 0.1$ and various values of material parameter K	102

Figure 5.6	Variation of the skin friction coefficient C_f for $K = 1$, $\gamma = 0.1$ and various values of material parameter Pr	103
Figure 5.7	Variation of the heat transfer coefficient Q_w for $K = 1$, $\gamma = 0.1$ and various values of material parameter Pr	103
Figure 5.8	Velocity profile $f'(y)$ for various values of K when $Pr = 7.0$, and $\gamma = 0.1$	104
Figure 5.9	Temperature profiles $\theta(y)$ for various values of K when $Pr = 7.0$ and $\gamma = 0.1$	104
Figure 5.10	Angular velocity profiles $G(y)$ for various values of K when $Pr = 7.0$ and $\gamma = 0.1$	105
Figure 5.11	Velocity profiles $f'(y)$ for various values of Pr when $\gamma = 0.1$ and $K = 1$	105
Figure 5.12	Temperature profiles $\theta(y)$ for various values of Pr when $\gamma = 0.1$ and $K = 1$	106
Figure 5.13	Angular velocity profiles $G(y)$ for various values of Pr when $\gamma = 0.1$ and $K = 1$	106
Figure 5.14	Velocity profiles $f'(y)$ for various values of γ when $Pr = 7.0$ and $K = 1$	107
Figure 5.15	Temperature profiles $\theta(y)$ for various values of γ when $Pr = 7.0$ and $K = 1$	107
Figure 5.16	Angular velocity profiles $G(y)$ for various values of γ when $Pr = 7.0$ and $K = 1$	108
Figure 6.1	Variation of the skin friction coefficient C_f for $\lambda = 1$, $\gamma = 0.1$ and various value of Pr	115
Figure 6.2	Variation of the heat transfer coefficient Q_w for $\lambda = 1$, $\gamma = 0.1$ and various values of Pr	116
Figure 6.3	Variation of the skin friction coefficient C_f for $\lambda = 1$, $Pr = 7.0$ and various value of γ	116
Figure 6.4	Variation of the heat transfer coefficient Q_w for $\lambda = 1$, $Pr = 7.0$ and various values of γ	117
Figure 6.5	Variation of the skin friction coefficient C_f for $Pr = 7.0$, $\gamma = 0.1$ and various value of λ	117
Figure 6.6	Variation of the heat transfer coefficient Q_w for $Pr = 7.0$, $\gamma = 0.1$ and various values of λ	118
Figure 6.7	Velocity profiles $f'(y)$ for various values of γ when $Pr = 7.0$, and $\lambda = 1$	118

Figure 6.8	Temperature profiles $\theta(y)$ for various values of γ when $Pr = 7.0$ and $\lambda = 1$	119
Figure 6.9	Velocity profiles $f'(y)$ for various values of Pr when $\gamma = 0.1$ and $\lambda = 1$	119
Figure 6.10	Temperature profiles $\theta(y)$ for various values of Pr when $\gamma = 0.1$ and $\lambda = 1$	120
Figure 6.11	Velocity profiles $f'(y)$ for various values of λ when $Pr = 7.0$ and $\gamma = 0.1$	120
Figure 6.12	Temperature profiles $\theta(y)$ for various values of λ when $Pr = 7.0$ and $\gamma = 0.1$	121
Figure 7.1	Comparison of the skin friction coefficient $Re_x^{1/2} C_f$ using Cu nanoparticles with $\phi = 0, 0.1, 0.2$, $\gamma = 0.1$, $Pr = 6.2$ and various values of λ	129
Figure 7.2	Comparison of the skin friction coefficient $Re_x^{1/2} C_f$ using Al_2O_3 nanoparticles with $\phi = 0, 0.1, 0.2$, $\gamma = 0.1$, $Pr = 6.2$ and various values of λ	130
Figure 7.3	Comparison of the skin friction coefficient $Re_x^{1/2} C_f$ using TiO_2 nanoparticles with $\phi = 0, 0.1, 0.2$, $\gamma = 0.1$, $Pr = 6.2$ and various values of λ	131
Figure 7.4	Comparison of the local Nusselt number $Re_x^{1/2} Nu$ using Cu nanoparticles with $\phi = 0, 0.1, 0.2$, $\gamma = 0.1$, $Pr = 6.2$ and various values of λ	131
Figure 7.5	Comparison of the local Nusselt number $Re_x^{1/2} Nu$ using Al_2O_3 nanoparticles with $\phi = 0, 0.1, 0.2$, $\gamma = 0.1$, $Pr = 6.2$ and various values of λ	132
Figure 7.6	Comparison of the local Nusselt number $Re_x^{1/2} Nu$ using TiO_2 nanoparticles with $\phi = 0, 0.1, 0.2$, $\gamma = 0.1$, $Pr = 6.2$ and various values of λ	132
Figure 7.7	Velocity profiles $f'(y)$ using Cu nanoparticles with $\gamma = 0.1$, $Pr = 6.2$, $\phi = 0, 0.1, 0.2$ and various values of λ	133
Figure 7.8	Velocity profiles $f'(y)$ using Al_2O_3 nanoparticles with $\gamma = 0.1$, $Pr = 6.2$, $\phi = 0, 0.1, 0.2$ and various values of λ	133
Figure 7.9	Velocity profiles $f'(y)$ using TiO_2 nanoparticles with $\gamma = 0.1$, $Pr = 6.2$, $\phi = 0, 0.1, 0.2$ and various values of λ	134
Figure 7.10	Temperature profiles $\theta(y)$ using Cu nanoparticles with $\gamma = 0.1$, $Pr = 6.2$, $\phi = 0, 0.1, 0.2$ and various values of λ	134

Figure 7.11	Temperature profiles $\theta(y)$ using Al_2O_3 nanoparticles with $\gamma = 0.1$, $\text{Pr} = 6.2$, $\phi = 0, 0.1, 0.2$ and various values of λ	135
Figure 7.12	Temperature profiles $\theta(y)$ using TiO_2 nanoparticles with $\gamma = 0.1$, $\text{Pr} = 6.2$, $\phi = 0, 0.1, 0.2$ and various values of λ	135
Figure 7.13	Comparison of the skin friction coefficient $\text{Re}_x^{1/2} C_f$ with $\phi = 0.1$, $\lambda = 1$, $\text{Pr} = 6.2$ and various values of γ	136
Figure 7.14	Comparison of the local Nusselt number $\text{Re}_x^{1/2} Nu$ with $\phi = 0.1$, $\gamma = 0.1$, $\text{Pr} = 6.2$ and various values of γ	136
Figure 7.15	Velocity profiles $f'(y)$ using various nanoparticles with $\text{Pr} = 6.2$, $\phi = 0.1$, $\lambda = 1$ and various values of γ	137
Figure 7.16	Temperature profiles $\theta(y)$ using various nanoparticles with $\text{Pr} = 6.2$, $\phi = 0.1$, $\lambda = 1$ and various values of γ	137
Figure 8.1	Physical model and coordinate system	140
Figure 8.2	Variation of the dimensionless skin friction coefficient $(\text{Pe}^{1/2}/\text{Pr})C_f$ for $Le = 2$, $\gamma = 0.05, 0.1, 0.2$, $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$ and $\lambda = 1$	145
Figure 8.3	Variation of the dimensionless heat flux coefficient $\text{Pe}^{1/2}Nu$ for $Le = 2$, $\gamma = 0.05, 0.1, 0.2$, $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$ and $\lambda = 1$	145
Figure 8.4	Variation of the dimensionless mass flux coefficient $\text{Pe}^{1/2}Sh$ for $Le = 2$, $\gamma = 0.05, 0.1, 0.2$, $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$ and $\lambda = 1$	146
Figure 8.5	Velocity profiles $f'(y)$ for various values of γ for $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$ and $\lambda = 1$	146
Figure 8.6	Temperature profiles $\theta(y)$ for various values of γ for $Le = 2$, $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$ and $\lambda = 1$	147
Figure 8.7	Nanoparticles volume fraction profiles $\phi(y)$ for various values of γ for $Le = 2$, $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$ and $\lambda = 1$	147
Figure 8.8	Variation of the dimensionless skin friction coefficient $(\text{Pe}^{1/2}/\text{Pr})C_f$ for $\lambda = 1$, $Le = 2, 6, 10$, $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$ and $\gamma = 0.1$	148
Figure 8.9	Variation of the dimensionless heat flux coefficient $\text{Pe}^{1/2}Nu$ for $\lambda = 1$, $Le = 2, 6, 10$, $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$ and $\gamma = 0.1$	148
Figure 8.10	Variation of the dimensionless mass flux coefficient $\text{Pe}^{1/2}Sh$ for $\lambda = 1$, $Le = 2, 6, 10$, $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$ and $\gamma = 0.1$	149
Figure 8.11	Velocity profiles $f'(y)$ for various values of Le for $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$, $\lambda = 1$ and $\gamma = 0.1$	149

Figure 8.12	Temperature profiles $\theta(y)$ for various values of Le for $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$, $\lambda = 1$ and $\gamma = 0.1$	150
Figure 8.13	Nanoparticles volume fraction profiles $\phi(y)$ for various values of Le for $Nb = 0.5$, $Nr = 0.5$, $Nt = 0.5$, $\lambda = 1$ and $\gamma = 0.1$	150
Figure 8.14	Variation of the skin friction coefficient $(Pe^{1/2}/Pr)C_f$ for $Le = 2$, $Nb = 0.1, 0.3, 0.5$, $Nr = 0.5$, $Nt = 0.1, 0.3, 0.5$, $\lambda = 1$ and $\gamma = 0.1$	151
Figure 8.15	Variation of the heat flux coefficient $Pe^{1/2}Nu$ for $Le = 2$, $Nb = 0.1, 0.3, 0.5$, $Nr = 0.5$, $Nt = 0.1, 0.3, 0.5$, $\lambda = 1$ and $\gamma = 0.1$	151
Figure 8.16	Variation of the mass flux coefficient $Pe^{1/2}Sh$ for $Le = 2$, $Nb = 0.1, 0.3, 0.5$, $Nr = 0.5$, $Nt = 0.1, 0.3, 0.5$, $\lambda = 1$ and $\gamma = 0.1$	152
Figure 8.17	Velocity profiles $f'(y)$ for various values of Nb and Nt for $Nr = 0.5$, $Le = 2$, $\lambda = 1$ and $\gamma = 0.1$	152
Figure 8.18	Temperature profiles $\theta(y)$ for various values of Nb and Nt for $Nr = 0.5$, $Le = 2$, $\lambda = 1$ and $\gamma = 0.1$	153

LIST OF SYMBOLS

a	Radius of cylinder
A	Area of the object
A_I	Rivlin-Ericksen tensor
A_m	Acceleration
C	Nanoparticle volume fraction
Cu	Copper/Cuprum
C_f	Skin friction coefficient
C_p	Specific heat
D_B	Brownian motion
D_T	Thermophoretic diffusion
e_t	Total energy
e_{int}	Kinetic energy
F_s	Surface forces
F_b	Body forces
f	Dimensionless stream function
Gr	Grashof number
G	Angular velocity
g	Gravity vector
h	Heat transfer coefficient
I	Identity tensor
h_f	Heat transfer coefficient
J	Microinertia per unit mass
K_1	Micropolar parameter
K_2	Permeability of the porous medium
k	Thermal conductivity
k_{nf}	Thermal conductivity of the nanofluids
k_s	Thermal conductivity of the solid
L	Length of the cylinder
Le	Lewis number
Nu	Nusselt number
N_b	Brownian motion parameter

N_r	Buoyancy ratio parameter
N_t	Thermophoresis parameter
Pe	Peclet number
p	Pressure
Pr	Prandtl number
Pr_c	Critical value of Prandtl number
q	Heat transfer per unit time
q_m	Mass flux
q_w	Heat flux
Ra	Rayleigh number
Re	Reynolds number
$S(t)$	Control surface
Sh	Sherwood number
T	Temperature
T_f	Temperature of the hot fluid
T_w	Local temperature
T_∞	Fluid temperature
U_∞	Free stream velocity
u, v	Velocity component in x, y direction
u_e	Free stream velocity
V	Fluid filtration velocity
$V(t)$	Control volume

Greek Symbol

α	Thermal diffusivity
α_{nf}	Thermal diffusivity of nanofluids
α_m	Effective thermal diffusivity
β	Thermal expansion coefficient
β_f	Thermal expansion coefficient of the fluid
β_s	Thermal expansion coefficient of the solid

δ	Boundary layer thickness
ε	Porosity of the porous medium
γ	Convective parameter
γ_c	Critical value of convective parameter
κ	Vortex viscosity
λ	Mixed convection parameter
μ	Viscosity
μ_f	Viscosity of the fluid fraction
ν	Kinematic viscosity
ϕ	Nanoparticle volume fraction
ψ	Stream function
ρ	Fluid density
ρ_p	Density of particle
ρ_{nf}	Density of nanofluid
ρ_{cm}	Effective heat capacity
$\rho_{f\infty}$	Density of the base fluid
τ	Shear stress
τ_w	Skin friction coefficient
θ	Nondimensional temperature
σ	Shear stress
ξ	Rate of shear

Subscripts

c	Critical value
f	Fluid
w	Surface condition
∞	Ambient condition
nf	Nanofluid
p	Particle

LIST OF ABBREVIATIONS

BVP	Boundary value problem
CBC	Convective boundary conditions
CHF	Constant heat flux
CWT	Constant wall temperature
CWFEM	Control volume finite element method
HAM	Homotopy analysis method
KBM	Keller-box method
MHD	Magnetohydrodynamic
NH	Newtonian heating
ODE	Ordinary differential equations
PDE	Partial differential equations
FDM	Finite difference method
FEM	Finite element method
FVM	Finite volume method
RKF	Runge-Kutta Fehlberg

REFERENCES

- Abbasi, F., Shehzad, S., Hayat, T., and Alhuthali, M. (2016). Mixed convection flow of jeffrey nanofluid with thermal radiation and double stratification. *Journal of Hydrodynamics, Ser. B*, 28(5):840 – 849.
- Abdallaoui, M. E., Hasnaoui, M., and Amahmid, A. (2015). Numerical simulation of natural convection between a decentered triangular heating cylinder and a square outer cylinder filled with a pure fluid or a nanofluid using the lattice boltzmann method. *Powder Technology*, 277:193 – 205.
- Abou-Ziyan, H., Kalender, A., Shedid, M., and Abdel-Hameed, H. (2017). Experimental investigation of free convection from short horizontal cylinder to newtonian and power-law liquids of large prandtl numbers. *Experimental Thermal and Fluid Science*, 86:102 – 116.
- Abu-Nada, E. and Oztop, H. F. (2009). Effect of inclination angle on natural convection in enclosures filled with Cu-water nanofluid. *Internation Journal Heat Fluid Flow*, 30(4):669 – 678.
- Acheson, D. (1990). *Elementary Fluid Dynamics*. Clarendon Press, Oxford, London.
- Acrivos, A. (1966). On the combined effect of forced and free convection heat transfer in laminar boundary layer flows. *Chemical Engineering Science*, 21(4):343 – 352.
- Ahmad, K., Nazar, R., and Pop, I. (2012). Mixed convection in laminar film flow of a micropolar fluid. *International Communications in Heat and Mass Transfer*, 39(1):36 – 39.
- Ahmad, S., Arifin, N., Nazar, R., and Pop, I. (2009). Mixed convection boundary layer flow past an isothermal horizontal circular cylinder with temperature-dependent viscosity. *International Journal of Thermal Sciences*, 48(10):1943 – 1948.
- Ahmad, S., Nazar, R., and Pop, I. (2005). Forced convection boundary layer flow over a horizontal circular cylinder with constant surface heat flux. Kedah Malaysia. Proceeding of the Simposium Kebangsaan Sains Matematik ke XIII.
- Alsaedi, A., Awais, M., and Hayat, T. (2012). Effects of heat generation/absorption on stagnation point flow of nanofluid over a surface with convective boundary conditions. *Communications in Nonlinear Science and Numerical Simulation*, 17(11):4210 – 4223.
- Altunkaya, A. N., Avci, M., and Aydin, O. (2017). Effects of viscous dissipation on mixed convection in a vertical parallel-plate microchannel with asymmetric uniform wall heat fluxes: The slip regime. *International Journal of Heat and Mass Transfer*, 111:495 – 499.
- Amin, N. and Riley, N. (1990). Horizontal free convection. *Proceedings of the Royal Society of London A: Mathematical, Physical and Engineering Sciences*, 427(1873):371–384.
- Anderson, J. D. J. (2005). Ludwig Prandtl's boundary layer. *American Institute of Physics*, 58(12):42 – 48.

- Anwar, I., Amin, N., and Pop, I. (2008). Mixed convection boundary layer flow of a viscoelastic fluid over a horizontal circular cylinder. *International Journal of Non-Linear Mechanics*, 43(9):814 – 821.
- Ariman, T., Turk, M., and Sylvester, N. (1973). Microcontinuum fluid mechanics —a review. *International Journal of Engineering Science*, 11(8):905 – 930.
- Ashorynejad, H. R., Mohamad, A. A., and Sheikholeslami, M. (2013). Magnetic field effects on natural convection flow of a nanofluid in a horizontal cylindrical annulus using Lattice Boltzmann method. *International Journal of Thermal Sciences*, 64:240 – 250.
- Aziz, A. (2009). A similarity solution for laminar thermal boundary layer over a flat plate with a convective surface boundary condition. *Communications in Nonlinear Science and Numerical Simulation*, 14(4):1064 – 1068.
- Aziz, A. and Khan, W. (2012). Natural convective boundary layer flow of a nanofluid past a convectively heated vertical plate. *International Journal of Thermal Sciences*, 52:83 – 90.
- Bachok, N., Ishak, A., and Pop, I. (2010). Boundary-layer flow of nanofluids over a moving surface in a flowing fluid. *International Journal of Thermal Sciences*, 49(9):1663 – 1668.
- Bachok, N., Ishak, A., and Pop, I. (2012). Unsteady boundary layer flow of a nanofluid over a permeable stretching/shrinking sheet. *International Journal and Heat Mass Transfer*, 55:2102 – 2109.
- Balaram, M. and Sastri, V. (1973). Micropolar free convection flow. *International Journal of Heat and Mass Transfer*, 16(2):437 – 441.
- Bejan, A. (2013). *Convection heat transfer (4th edition)*. John Wiley and Sons., New York.
- Bhargava, R. and Takhar, H. (2000). Numerical study of heat transfer characteristics of the micropolar boundary layer near a stagnation point on a moving wall. *International Journal of Engineering Science*, 38(4):383 – 394.
- Bharti, R. P., Chhabra, R. P., and Eswaran, V. (2007). Steady forced convection heat transfer from a heated circular cylinder to power-law fluids. *International Journal of Heat and Mass Transfer*, 50(7):977 – 990.
- Bhattacharyya, S. and Pop, I. (1996). Free convection from cylinders of elliptic cross-section in micropolar fluids. *International Journal of Engineering Science*, 34(11):1301 – 1310.
- Bhowmick, S., Molla, M. M., Mia, M., and Saha, S. C. (2014). Non-newtonian mixed convection flow from a horizontal circular cylinder with uniform surface heat flux. *Procedia Engineering*, 90:510 – 516.
- Birkhauser, G. L. (1999). Micropolar fluids: Theory and applications. *Journal of Fluid Mechanics*, 401(1):378 – 381.
- Blasius, H. (1908). The boundary layer in fluid with little friction. *Journal of Applied Mathematics and Physics*, 56(60):397 – 398.

- Borrelli, A., Giancesio, G., and Patria, M. C. (2013). Numerical simulations of three-dimensional mhd stagnation-point flow of a micropolar fluid. *Computers & Mathematics with Applications*, 66(4):472 – 489.
- Botte, G. G., Subramanian, V. R., and White, R. E. (2000). Mathematical modeling of secondary lithium batteries. *Electrochimica Acta*, 45:25952609.
- Buongiorno, J. (2006). Convective transport in nanofluids. *Journal of Heat Transfer*, 128:240 – 250.
- Cebeci, T. and Bradshaw, P. (1988). *Physical and Computational Aspects of Convective Heat Transfer*. Springer, New York.
- Chaudhary, R. C. and Jain, P. (2006). Unsteady free convection boundary-layer flow past an impulsively started vertical surface with newtonian heating. *Romanian Journal of Physics*, 9:911 – 925.
- Cheng, P. (1982). Mixed convection about a horizontal cylinder and sphere in a fluid-saturated porous medium. *International Journal of Heat and Mass Transfer*, 25:1245 – 1246.
- Cheng, P. and Minkowycz, W. J. (1977). Free convection about a vertical flat plate embedded in a porous medium with application to heat transfer from a dike. *Journal of Geophysical Research*, 82(14):2040 – 2044.
- Choi, U. S. (1995). Enhancing thermal conductivity of fluids with nanoparticles. San Francisco, CA. ASME International Mechanical Engineering Congress and Exposition.
- Darus, A. N. (1994). *Analisis Pemindahan Haba*. Dewan Bahasa dan Pustaka, Kuala Lumpur.
- Das, K., Duari, P. R., and Kundu, P. K. (2015). Numerical simulation of nanofluid flow with convective boundary condition. *Journal of the Egyptian Mathematical Society*, 23(2):435 – 439.
- Daunghongsuk, W. and Wongwises, S. (2007). A critical review of convective heat transfer of nanofluids. *Renewable and Sustainable Energy Reviews*, 11(5):797 – 817.
- Dawood, H., Mohammed, H., Sidik, N. A. C., Munisamy, K., and Wahid, M. (2015). Forced, natural and mixed-convection heat transfer and fluid flow in annulus: A review. *International Communications in Heat and Mass Transfer*, 62:45 – 57.
- Deka, R. K., Paul, A., and Chaliha, A. (2017). Transient free convection flow past vertical cylinder with constant heat flux and mass transfer. *Ain Shams Engineering Journal*, 8(4):643 – 651.
- Dhanai, R., Rana, P., and Kumar, L. (2016). Mhd mixed convection nanofluid flow and heat transfer over an inclined cylinder due to velocity and thermal slip effects: Buongiorno's model. *Powder Technology*, 288:140 – 150.
- Dinarvand, S. and Pop, I. (2017). Free-convective flow of copper/water nanofluid about a rotating down-pointing cone using Tiwari-Das nanofluid scheme. *Advanced Powder Technology*, 28(3):900 – 909.

- Ding, Y., Chen, H., Wang, L., Yang, C.-Y., He, Y., Yang, W., Lee, W. P., Zhang, L., and Huo, R. (2007). Heat transfer intensification using nanofluids. *KONA Powder and Particle Journal*, 25:23 – 38.
- Durgam, S., Venkateshan, S., and Sundararajan, T. (2017). Experimental and numerical investigations on optimal distribution of heat source array under natural and forced convection in a horizontal channel. *International Journal of Thermal Sciences*, 115:125 – 138.
- Eastman, J. A., Choi, U. S., Li, S., Thompson, L. J., and Lee, S. (1997). Enhanced thermal conductivity through the development of nanofluids. Pittsburgh. MRS.
- Eckert, E. (1942). The calculation of the heat transfer in the laminar boundary layer around bodies. *VDI-Forschungsheft*, 416:1 – 24.
- Eiyad, A.-N., Ziyad, K., Saleh, M., and Ali, Y. (2008). Heat transfer enhancement in combined convection around a horizontal cylinder using nanofluids. *Journal of Heat Transfer*, 130(8):084505.
- Elgazery, N. S. and Elazem, N. Y. A. (2009). The effect of variable thermal conductivity on micro-polar fluid flow by chebyshev collocation method. *Chemical Engineering Communications*, 197(3):400 – 422.
- Elliott, L. (1970). Free convection on a two dimensional or axisymmetric body. *Journal Mechanical Applied Mathematics*, 23(5):153 – 162.
- Elsherbiny, S. M., Teamah, M. A., and Moussa, A. R. (2017). Experimental mixed convection heat transfer from an isothermal horizontal square cylinder. *Experimental Thermal and Fluid Science*, 82:459 – 471.
- Eringen, A. (1966). Theory of micropolar fluids. *Journal of Mathematics and Mechanics*, 16:1 – 18.
- Eringen, A. (1972). Theory of thermomicrofluids. *Journal of Mathematical Analysis and Applications*, 38(2):480 – 496.
- Frössling, N. (1940). Evaporation, heat transfer and velocity distribution in two-dimensional and rotationally symmetrical laminar boundary-layer flow. *Lunds. University Arsskr. NF Avdanced 2*, 35(4):2 – 38.
- Garoosi, F., Jahanshaloo, L., and Garoosi, S. (2015). Numerical simulation of mixed convection of the nanofluid in heat exchangers using a buongiorno model. *Powder Technology*, 269:296 – 311.
- Gibanov, N. S., Sheremet, M. A., and Pop, I. (2016). Free convection in a trapezoidal cavity filled with a micropolar fluid. *International Journal of Heat and Mass Transfer*, 99:831 – 838.
- Gorla, R. S. R. (1995). Unsteady mixed convection in micropolar boundary layer flow on a vertical plate. *Fluid Dynamics Research*, 15(4):237.
- Gruyter., D. (2014). *Keller-Box Method and Its Application*. Higher Education Press., Berlin, Boston.

- Hajmohammadi, M., Maleki, H., Lorenzini, G., and Nourazar, S. (2015). Effects of Cu and Ag nano-particles on flow and heat transfer from permeable surfaces. *Advanced Powder Technology*, 26(1):193 – 199.
- Hassani, M., Tabar, M. M., Nemati, H., Domairry, G., and Noori, F. (2011). An analytical solution for boundary layer flow of a nanofluid past a stretching sheet. *International Journal of Thermal Sciences*, 50(11):2256 – 2263.
- Hassanien, A. I. (1997). Combined forced and free convection in boundary layer flow of a micropolar fluid over a horizontal plate. *Journal Applied Mathematics and Physics*, 48(4):571 – 583.
- Hassanien, I. A. and Gorla, R. S. R. (1990). Combined forced and free convection in stagnation flows of micropolar fluids over vertical non-isothermal surfaces. *International Journal of Engineering Science*, 28(8):783 – 792.
- Hayat, T., Khan, M. I., Waqas, M., and Alsaedi, A. (2017). Newtonian heating effect in nanofluid flow by a permeable cylinder. *Results in Physics*, 7:256 – 262.
- Hussanan, A., Salleh, M. Z., Khan, I., and Shafie, S. (2017). Convection heat transfer in micropolar nanofluids with oxide nanoparticles in water, kerosene and engine oil. *Journal of Molecular Liquids*, 229:482 – 488.
- Ibrahim, F. and Hassanien, I. (2001). Local nonsimilarity solutions for mixed convection boundary layer flow of a micropolar fluid on horizontal flat plates with variable surface temperature. *Applied Mathematics and Computation*, 122(2):133 – 153.
- Incropera, F. P., DeWitt, D. P., Bergman, T. L., and Lavine, A. S. (2006). *Fundamentals of Heat and Mass Transfer*. John Wiley and Sons., New York.
- Ishak, A. (2010). Thermal boundary layer flow over a stretching sheet in a micropolar fluid with radiation effect. *Meccanica*, 45(3):367 – 373.
- Ishak, A., Nazar, R., and Pop, I. (2009). Dual solutions in mixed convection boundary layer flow of micropolar fluids. *Communications in Nonlinear Science and Numerical Simulation*, 14(4):1324 – 1333.
- Ishak, A., Yacob, N. A., and Bachok, N. (2011). Radiation effects on the thermal boundary layer flow over a moving plate with convective boundary condition. *Meccanica*, 46(4):795 – 801.
- Ismael, M. A., Mansour, M., Chamkha, A. J., and Rashad, A. (2016). Mixed convection in a nanofluid filled-cavity with partial slip subjected to constant heat flux and inclined magnetic field. *Journal of Magnetism and Magnetic Materials*, 416:25 – 36.
- Jena, S. and Mathur, M. (1981). Similarity solutions for laminar free convection flow of a thermomicro-polar fluid past a non-isothermal vertical flat plate. *International Journal of Engineering Science*, 19(11):1431 – 1439.
- Joshi, N. and Sukhatme, S. (1971). An analysis of combined free and forced convection heat transfer from a horizontal circular cylinder to a transverse flow. *ASME. J. Heat Transfer*, 93(4):343 – 352.

- Kaprawi, S. and Santoso, S. (2012). Convective heat transfer from a heated elliptical cylinder at uniform wall temperature. *International Journal of Energy and Environment*, 3(1):133 – 140.
- Kasim, A. R. M. (2014). *Convective Boundary Layer Flow of Viscoelastic Fluid*. Ph.D Thesis, Universiti Teknologi Malaysia.
- Kefayati, G. (2017). Mixed convection of non-newtonian nanofluid in an enclosure using Buongiorno's mathematical model. *International Journal of Heat and Mass Transfer*, 108, Part B:1481 – 1500.
- Keller, H. (1970). *A New Difference Method for Parabolic Problems In: Bramble, J., Ed., Numerical Methods for Partial Differential Equations*. Academic Press, New York.
- Kelson, N. and Desseaux, A. (2001). Effect of surface conditions on flow of a micropolar fluid driven by a porous stretching sheet. *International Journal of Engineering Science*, 39(16):1881 – 1897.
- Khan, J. A., Mustafa, M., and Mushtaq, A. (2016). On three-dimensional flow of nanofluids past a convectively heated deformable surface: A numerical study. *International Journal of Heat and Mass Transfer*, 94:49 – 55.
- Khan, W. and Aziz, A. (2011). Double-diffusive natural convective boundary layer flow in a porous medium saturated with a nanofluid over a vertical plate: Prescribed surface heat, solute and nanoparticle fluxes. *International Journal of Thermal Sciences*, 50(11):2154 – 2160.
- Khan, W., Culham, J., and Yovanovich, M. (2004). Fluid flow around and heat transfer from an infinite circular cylinder. *ASME. Journal Heat Transfer*, 127(7):785 – 790.
- Khan, W. and Pop, I. (2010). Boundary-layer flow of a nanofluid past a stretching sheet. *International Journal of Heat and Mass Transfer*, 53(11):2477 – 2483.
- Khanafer, K., Vafai, K., and Lightstone, M. (2003). Buoyancy-driven heat transfer enhancement in a two-dimensional enclosure utilizing nanofluids. *International Journal of Heat and Mass Transfer*, 46(19):3639 – 3653.
- Kim, Y. J. and Lee, J.-C. (2003). Analytical studies on mhd oscillatory flow of a micropolar fluid over a vertical porous plate. *Surface and Coatings Technology*, 171(13):187 – 193.
- Kuznetsov, A. and Nield, D. (2010). Natural convective boundary-layer flow of a nanofluid past a vertical plate. *International Journal of Thermal Sciences*, 49(2):243 – 247.
- Kuznetsov, A. and Nield, D. (2011). Double-diffusive natural convective boundary-layer flow of a nanofluid past a vertical plate. *International Journal of Thermal Sciences*, 50(5):712 – 717.
- Mabood, F., Ibrahim, S., Kumar, P., and Khan, W. (2017). Viscous dissipation effects on unsteady mixed convective stagnation point flow using Tiwari-Das nanofluid model. *Results in Physics*, 7:280 – 287.
- Mabood, F., Khan, W., and Yovanovich, M. (2016). Forced convection of nanofluid flow across horizontal circular cylinder with convective boundary condition. *Journal of Molecular Liquids*, 222:172 – 180.

- Magyari, E. (2011). Comment on a similarity solution for laminar thermal boundary layer over a flat plate with a convective surface boundary condition by A. Aziz. *Communications in Nonlinear Science and Numerical Simulation*, 16(1):599 – 601.
- Magyari, E. and Keller, B. (2001). Exact analytical solutions of forced convection flow in a porous medium. *International Communication. Heat Mass Transfer*, 28(2):233 – 241.
- Mahfouz, F. (2013). Numerical simulation of free convection within an eccentric annulus filled with micropolar fluid using spectral method. *Applied Mathematics and Computation*, 219(10):5397 – 5409.
- Mahgoub, S. (2013). Forced convection heat transfer over a flat plate in a porous medium. *Ain Shams Engineering Journal*, 4(4):605 – 613.
- Maiti, G. (1975). Convective heat transfer in micropolar fluid flow through a horizontal parallel plate channel. *Journal of Applied Mathematics and Mechanics*, 55(2):105–111.
- Makinde, O. and Aziz, A. (2011). Boundary layer flow of a nanofluid past a stretching sheet with a convective boundary condition. *International Journal of Thermal Sciences*, 50(7):1326 – 1332.
- Malik, M., Jamil, H., Salahuddin, T., Bilal, S., Rehman, K., and Mustafa, Z. (2016). Mixed convection dissipative viscous fluid flow over a rotating cone by way of variable viscosity and thermal conductivity. *Results in Physics*, 6:1126 – 1135.
- Mansour, M., El-Hakiem, M., and Kabeir, S. E. (2000). Heat and mass transfer in magnetohydrodynamic flow of micropolar fluid on a circular cylinder with uniform heat and mass flux. *Journal of Magnetism and Magnetic Materials*, 220(23):259 – 270.
- Mansur, S. and Ishak, A. (2013). The flow and heat transfer of a nanofluid past a stretching/shrinking sheet with a convective boundary condition. *Abstract and Applied Analysis*, 2013:1 – 9.
- Martynenko, O. and Khramtsov, P. (2005). *Free Convective Heat Transfer*. Springer, Springer Berlin Heidelberg, New York.
- Mathur, M., Ojha, S., and Ramachandran, P. (1978). Thermal boundary layer of a micropolar fluid on a circular cylinder. *International Journal of Heat and Mass Transfer*, 21:923 – 933.
- Merkin, J. (1976). Free convection boundary layer on an isothermal horizontal circular cylinders. St. Louis, Mo. ASME/AIChE Heat transfer conference.
- Merkin, J. (1977). Mixed convection from a horizontal circular cylinder. *International Journal of Heat and Mass Transfer*, 20(1):73 – 77.
- Merkin, J. (1994). Natural-convection boundary-layer flow on a vertical surface with newtonian heating. *International Journal of Heat and Fluid Flow*, 15(5):392 – 398.
- Merkin, J. and Pop, I. (2011). The forced convection flow of a uniform stream over a flat surface with a convective surface boundary condition. *Communications in Nonlinear Science and Numerical Simulation*, 16(9):3602 – 3609.

- Merkin, J. H. and Pop, I. (1988). A note on the free convection boundary layer on a horizontal circular cylinder with constant heat flux. *Wärme - und Stoffübertragung*, 22(1):79 – 81.
- Mirgolbabaei, H., Barari, A., Ibsen, L., and Sfahani, M. (2010). Analytical solution of forced-convective boundary-layer flow over a flat plate. *Archives of Civil and Mechanical Engineering*, 10(2):41 – 51.
- Mohamed, M. K. A. (2013). *Mathematical modelling for the convection boundary layer flow in a viscous fluid with Newtonian heating and convective boundary conditions*. MSc Thesis, Universiti Malaysia Pahang.
- Mohammed, H. A. and Salman, Y. K. (2007). Free and forced convection heat transfer in the thermal entry region for laminar flow inside a circular cylinder horizontally oriented. *Energy Conversion and Management*, 48(7):2185 – 2195.
- Mohd Rohni, A., Ahmad, S., and Pop, I. (2013). Forced convection boundary layer flow along a horizontal cylinder in porous medium filled by nanofluid. *International Journal of Humanities and Management Sciences*, 1(1):23 – 27.
- Moshizi, S., Zamani, M., Hosseini, S., and Malvandi, A. (2017). Mixed convection of magnetohydrodynamic nanofluids inside microtubes at constant wall temperature. *Journal of Magnetism and Magnetic Materials*, 430:36 – 46.
- Mukhopadhyay, S. (2012). Mixed convection boundary layer flow along a stretching cylinder in porous medium. *Journal of Petroleum Science and Engineering*, 9697:73 – 78.
- Mukhopadhyay, S. and Mandal, I. C. (2015). Magnetohydrodynamic (MHD) mixed convection slip flow and heat transfer over a vertical porous plate. *Engineering Science and Technology, an International Journal*, 18(1):98 – 105.
- Na, T. Y. (1979). *Computational Methods in Engineering Boundary Value Problems*. Academic Press, New York.
- Nadeem, S., Mehmood, R., and Akbar, N. S. (2014). Optimized analytical solution for oblique flow of a Casson-nano fluid with convective boundary conditions. *International Journal of Thermal Sciences*, 78:90 – 100.
- Nakai, S. and Okazaki, T. (1975). Heat transfer from a horizontal circular wire at small Reynolds and Grashof numbers. *International Journal Heat Mass Transfer*, 18:397 – 413.
- Nayak, R., Bhattacharyya, S., and Pop, I. (2015). Numerical study on mixed convection and entropy generation of Cu - water nanofluid in a differentially heated skewed enclosure. *International Journal of Heat and Mass Transfer*, 85:620 – 634.
- Nazar, R. (2003). *Mathematical model for free and mixed convection boundary layer flows of micropolar fluids*. Ph.D Thesis, Universiti Teknologi Malaysia.
- Nazar, R., Amin, N., Groan, T., and Pop, I. (2002a). Free convection boundary layer on a sphere with constant surface heat flux in a micropolar fluid. *International Communications in Heat and Mass Transfer*, 29(8):1129 – 1138.
- Nazar, R., Amin, N., and Pop, I. (2002b). Free convection boundary layer on an isothermal horizontal circular cylinder in a micropolar fluid. *Heat Transfer*, 2:525 – 530.

- Nazar, R., Amin, N., and Pop, I. (2003). Mixed convection boundary-layer flow from a horizontal circular cylinder in micropolar fluids: case of constant wall temperature. *International Journal of Numerical Methods for Heat & Fluid Flow*, 13(1):86 – 109.
- Nazar, R., Amin, N., and Pop, I. (2004). Mixed convection boundary-layer flow from a horizontal circular cylinder with a constant surface heat flux. *Heat and Mass Transfer*, 40(3-4):219 – 227.
- Nield, D. and Kuznetsov, A. (2009). The Cheng-Minkowycz problem for natural convective boundary-layer flow in a porous medium saturated by a nanofluid. *International Journal of Heat and Mass Transfer*, 52(25-26):5792 – 5795.
- Nield, D. A. and Kuznetsov, A. V. (2011). The Cheng-Minkowycz problem for the double-diffusive natural convective boundary layer flow in a porous medium saturated by a nanofluid. *International Journal of Heat and Mass Transfer*, 54:5 – 9.
- Othman, N. A., Yacob, N. A., Bachok, N., Ishak, A., and Pop, I. (2017). Mixed convection boundary-layer stagnation point flow past a vertical stretching/shrinking surface in a nanofluid. *Applied Thermal Engineering*, 115:1412 – 1417.
- Oztop, H. F. and Abu-Nada, E. (2008). Numerical study of natural convection in partially heated rectangular enclosures filled with nanofluids. *International Journal of Heat and Fluid Flow*, 29(5):1326 – 1336.
- Pantokratoras, A. (2014). A note on natural convection along a convectively heated vertical plate. *International Journal of Thermal Sciences*, 76:221 – 224.
- Peddieson, J. and McNitt, R. P. (1970). Boundary layer theory for micropolar fluid. *Recent Advance Engineering Science*, 5:405 – 426.
- Rahmati, A. R., Roknabadi, A. R., and Abbaszadeh, M. (2016). Numerical simulation of mixed convection heat transfer of nanofluid in a double lid-driven cavity using Lattice Boltzmann method. *Alexandria Engineering Journal*, 55(4):3101 – 3114.
- RamReddy, C., Murthy, P., Chamkha, A. J., and Rashad, A. (2013). Soret effect on mixed convection flow in a nanofluid under convective boundary condition. *International Journal of Heat and Mass Transfer*, 64:384 – 392.
- Ramzan, M., Bilal, M., Farooq, U., and Chung, J. D. (2016). Mixed convective radiative flow of second grade nanofluid with convective boundary conditions: An optimal solution. *Results in Physics*, 6:796 – 804.
- Rebhi, A. D., Tariq, A. A., Benbella, A. S., and Mahmoud, A. (2007). Unsteady natural convection heat transfer of micropolar fluid over a vertical surface with constant heat flux. *Turkish Journal Engineering Environment Science*, 31:225 – 233.
- Roca, N. C. and Pop, I. (2013). Mixed convection stagnation point flow past a vertical flat plate with a second order slip: Heat flux case. *International Journal of Heat and Mass Transfer*, 65:102 – 109.
- Sajid, M., Abbas, Z., and Hayat, T. (2009). Homotopy analysis for boundary layer flow of a micropolar fluid through a porous channel. *Applied Mathematical Modelling*, 33(11):4120 – 4125.

- Sakai, F., Li, W., and Nakayama, A. (2014). A rigorous derivation and its applications of volume averaged transport equations for heat transfer in nanofluids saturated metal foam. *Proc. 15th International Heat Transfer Conference*, 23(2):435 – 439.
- Salleh, M. Z. and Nazar, R. (2010). Free convection boundary layer flow over a horizontal circular cylinder with Newtonian heating. *Sains Malaysiana*, 39(4):671 – 676.
- Salleh, M. Z., Nazar, R., Arifin, N., and Pop, I. (2011). Numerical solutions of forced convection boundary layer flow on a horizontal circular cylinder with Newtonian heating. *Malaysian Journal of Mathematical Sciences*, 5(2):161 – 184.
- Salleh, M. Z., Nazar, R., and Pop, I. (2009). Forced convection boundary layer flow at a forward stagnation point with Newtonian heating. *Chemical Engineering Communications*, 196(9):987 – 996.
- Salleh, M. Z., Nazar, R., and Pop, I. (2010a). Boundary layer flow and heat transfer over a stretching sheet with Newtonian heating. *Journal of the Taiwan Institute of Chemical Engineers*, 41(6):651 – 655.
- Salleh, M. Z., Nazar, R., and Pop, I. (2010b). Mixed convection boundary layer flow over a horizontal circular cylinder with Newtonian heating. *Heat and Mass Transfer*, 46(11):1411 – 1418.
- Samyuktha, N. and Ravindran, R. (2015). Thermal radiation effect on mixed convection flow over a vertical stretching sheet embedded in a porous medium with suction (injection). *Procedia Engineering*, 127:767 – 774.
- Sanitjai, S. and Goldstein, R. (2004). Forced convection heat transfer from a circular cylinder in crossflow to air and liquids. *International Journal of Heat and Mass Transfer*, 47(22):4795 – 4805.
- Sastry, V. U. K. and Maity, G. (1976). Numerical solution of combined convective heat transfer of micropolar fluid in an annulus of two vertical pipes. *International Journal of Heat and Mass Transfer*, 19:207 – 211.
- Schlichting, H. (1968). *Boundary Layer Theory 8th Edition*. Springer Inc.
- Seshadri, R. and Munjam, S. R. (2016). Mixed convection flow due to a vertical plate in the presence of heat source and chemical reaction. *Ain Shams Engineering Journal*, 7(2):671 – 682.
- Seyyedi, S., Dayyan, M., Soleimani, S., and Ghasemi, E. (2015). Natural convection heat transfer under constant heat flux wall in a nanofluid filled annulus enclosure. *Ain Shams Engineering Journal*, 6(1):267 – 280.
- Sheikholeslami, M. and Bhatti, M. (2017). Forced convection of nanofluid in presence of constant magnetic field considering shape effects of nanoparticles. *International Journal of Heat and Mass Transfer*, 111:1039 – 1049.
- Sheikholeslami, M. and Ganji, D. (2016). Nanofluid convective heat transfer using semi analytical and numerical approaches: A review. *Journal of the Taiwan Institute of Chemical Engineers*, 65:43 – 77.

- Sheremet, M. A., Grosan, T., and Pop, I. (2015). Free convection in a square cavity filled with a porous medium saturated by nanofluid using Tiwari and Das' nanofluid model. *Transport in Porous Media*, 106(3):595 – 610.
- Sheremet, M. A. and Pop, I. (2015). Free convection in a porous horizontal cylindrical annulus with a nanofluid using Buongiorno's model. *Computers Fluids*, 118:182 – 190.
- Shu, J. J. and Wilks, G. (1995). An accurate numerical method for systems of differential-integral equations associated with multiphase flow. *Computers & Fluids*, 24(6):625 – 652.
- Soares, A. A., Ferreira, J. M., and Chhabra, R. P. (2005). Flow and forced convection heat transfer in crossflow of non-newtonian fluids over a circular cylinder. *Industrial & Engineering Chemistry Research*, 44(15):5815 – 5827.
- Soleimani, S., Sheikholeslami, M., Ganji, D., and Gorji-Bandpay, M. (2012). Natural convection heat transfer in a nanofluid filled semi-annulus enclosure. *International Communications in Heat and Mass Transfer*, 39(4):565 – 574.
- Sparrow, E. and Lee, L. (1976). Analysis of mixed convection about a horizontal cylinder. *International Journal of Heat and Mass Transfer*, 19(2):229 – 232.
- Sumaily, G. F. A., Sheridan, J., Ibsen, and Thompson, M. C. (2012). Analysis of forced convection heat transfer from a circular cylinder embedded in a porous medium. *International Journal of Thermal Sciences*, 51:121 – 131.
- Takhar, H. S., Agarwal, R. S., and Bhargava, R. (1998). Mixed convection flow of a micropolar fluid over a stretching sheet. *Heat and Mass Transfer*, 34(2):213 – 219.
- Tham, L., Nazar, R., and Pop, I. (2012). Mixed convection boundary layer flow from a horizontal circular cylinder in a nanofluid. *International Journal of Numerical Methods for Heat & Fluid Flow*, 22(5):576 – 606.
- Tham, L., Nazar, R., and Pop, I. (2014). Mixed convection flow from a horizontal circular cylinder embedded in a porous medium filled by a nanofluid: Buongiorno-Darcy model. *International Journal of Thermal Sciences*, 84:21 – 33.
- Tiwari, R. K. and Das, M. K. (2007). Heat transfer augmentation in a two-sided lid-driven differentially heated square cavity utilizing nanofluids. *International Journal of Heat and Mass Transfer*, 50(910):2002 – 2018.
- Vimala, S., Damodaran, S., Sivakumar, R., and Sekhar, T. (2016). The role of magnetic Reynolds number in Magnetohydrodynamic forced convection heat transfer. *Applied Mathematical Modelling*, 40(1314):6737 – 6753.
- Waqas, M., Farooq, M., Khan, M. I., Alsaedi, A., Hayat, T., and Yasmeen, T. (2016). Magnetohydrodynamic mixed convection flow of micropolar liquid due to nonlinear stretched sheet with convective condition. *International Journal of Heat and Mass Transfer*, 102:766 – 772.
- Willson, A. J. (1969). Basic flows of a micropolar liquid. *Applied Scientific Research*, 20(1):338 – 355.

- Xuan, Y. and Li, Q. (2000). Heat transfer enhancement of nanofluids. *International Journal Heat Fluid Flow*, 21:58 – 64.
- Yacob, N. A., Ishak, A., Pop, I., and Vajravelu, K. (2011). Boundary layer flow past a stretching/shrinking surface beneath an external uniform shear flow with a convective surface boundary condition in a nanofluid. *Nanoscale Research Letters*, 6(1):314.
- Zhang, P., Zhang, X., Deng, J., and Song, L. (2016). A numerical study of natural convection in an inclined square enclosure with an elliptic cylinder using variational multiscale element free galerkin method. *International Journal of Heat and Mass Transfer*, 99:721 – 737.
- Zukauskas, A. and Ziugzda, J. (1985). Heat transfer of a cylinder in crossflow. *International Journal of Engineering Science*, 44(1-2):949 – 958.